

The CT-600 series constant temperature bath, with its external thermoelectric cooler, accommodates viscometer tubes requiring a bath depth up to 12" and provides reliable temperature control from 10 °C to 100 °C. The unit accommodates up to 7 simultaneous viscosity determinations.

Common Applications

- Formulated oil analysis
- Hydraulic oil analysis
- Additive analysis
- Marine fuel testing
- Base stock analysis
- Light and heavy fuel testing
- Waxes/paraffin
- Crude oil testing
- Glycols

CT-600 Constant Temperature Bath

For Kinematic Viscosity from 10 °C to 100 °C
ASTM D445/D446, ISO 3104/3105

Precise & accurate temperature control

- Temperature range: 10 °C to 100 °C ± 0.01 °C
- Temperature selection is variable between 10 °C and 100 °C or selectable at ten pre-set temperatures (10 °C, 15 °C, 20 °C, 25 °C, 30 °C, 40 °C, 50 °C, 60 °C, 80 °C and 100 °C)
- Meets ASTM D445 temperature sensitivity requirements for kinematic viscosity determination
- Motor driven stirrer ensures a uniform bath temperature

Safe operation

- Bath thermistor senses over-temperature fault and removes power
- Thermistor disconnection results in removal of bath heater power
- Liquid level sensor prevents operation if bath liquid is not at a safe operating level

Efficient, user-friendly design

- Seven glass viscometer ports (each 2" in diameter) and two thermometer ports (each 0.4" in diameter) allow up to 7 simultaneous viscosity determinations*
- Two electric heating elements quickly heat bath media to the selected temperature
- Stainless steel baffle provides a plain reflective viewing background
- Convenient drawer provides easy access to electrical controls

Reliable performance

- Well tested CANNON bath platform offers reliability and dependable support
- All wetted components are manufactured from high quality stainless steel or glass
- The heavy duty aluminum frame offers a corrosion-resistant epoxy finish



2139 High Tech Road | State College | PA | 16803
800-676-6232 | 814-353-8000 | Fax 814-353-8007
sales@cannoninstrument.com | cannoninstrument.com

CT-600 | Constant Temperature Bath

Ordering Information

CT-600 Constant Temperature Bath consists of the bath unit and viscometer port covers. Vicometer tubes, holders, bath oil and thermometer sold separately.

Description	Part #
120 VAC, 50/60 Hz	9726-A36
240 VAC, 50/60 Hz	9726-A37

Accessories & Consumables

Description	Part #
Glass viscometers & holders	various
Storage drawer	9726-A50
Port cover set (7 covers; 2 thermometer holders)	22.39
Bath oils	
IBF oxidation resistant bath oil (22.7 L/6 gal)	9726-L20
Silicone bath oil, 10 cSt (18.9 L, 5 gal)	9726-L30
Silicone bath oil, 20 cSt (18.9 L, 5 gal)	9726-L33
Silicone bath oil, 50 cSt (18.9 L, 5 gal)	9726-L36
Dostmann digital thermometer	61.5600
Standard thermometer probe	61.5601
CANNON pressure/vacuum pump	9726-L96
3VM vacuum manifold, 3 valves	9726-V10
4VM vacuum manifold, 4 valves	9726-V05
Neoprene vacuum tubing, 10 ft (1/4 in bore x 5/8 in OD)	9726-V23
DVR-3000	9726-T70

Product Specifications

Dimensions (W x D x H)	40.7 cm x 36.2 cm x 83.2 cm (16 in x 14.25 in x 32.8 in)
Weight	25.6 kg (56.5 lb)
Shipping dimensions (W x D x H)	76.2 cm x 58.4 cm x 55.9 cm (30 in x 23 in x 22 in)
Shipping weight (with all items)	36.3 kg (80 lb)
Temperature range & accuracy	10 °C to 100 °C ± 0.01 °C
Sample capacity	7
Bath height	12 in
Bath volume	17 L (4.5 gal)
Operating conditions	15 °C to 30 °C, 10% to 75% relative humidity (non-condensing), Installation Category II; Pollution Degree 2
Electrical specifications	120 VAC, 50/60 Hz; 240 VAC, 50/60 Hz; 1,300 watts power consumption
Compliance	CE Mark; EMC directive (2004/108/EC); Low voltage directive (2006/95/EC); HI-POT (1900 VDC, 60 sec.); ROHS

*Other port configurations are available as a special order.

CANNON Instrument Company® provides a variety of physical property testing equipment and consumables (vials, bath fluids, and reference materials) for your testing needs. To learn more, contact sales@cannoninstrument.com.



2139 High Tech Road | State College | PA | 16803
800-676-6232 | 814-353-8000 | Fax 814-353-8007

sales@cannoninstrument.com | cannoninstrument.com