

Automated Micro Carbon Residue Tester

Micro Carbon Residue Tester

ACR-100m

NEW

Connectable to Electronic Balance

Weight values can be imported and test results are calculated automatically.

Equipped with Printing Function

Printing is available if a printer is connected.

LCD Touch Screen

Equipped with a touch screen for simple, intuitive operation.

Interlock Safety Function

Cannot be started unless the lid is in place.

Cleaning the Oven Seal Lid Assembly

Possible to burn off the dirt from the lid assembly by leaving it in a coking oven.



Test Results

Results from the last 6 test runs can be stored.

Specifications

CE UK
CA

Test Methods	ASTM D4530, ISO 10370, JIS K2270-2
Measuring Range	Ambient to 500 °C
Heating / Cooling	Pipe Heater / Air Cooling
I/O Port	SD Card x 1, Ethernet x 1 (Printer / LIMS), RS-232C x1
Dimensions	W 380 mm x D 480 mm x H 480 mm
Weight	25 kg
Power Consumption	AC 100 V to 120 V 50 / 60 Hz 1500 VA AC 220 V to 240 V 50 / 60 Hz 1500 VA

TANAKA reserves the right of changes without prior notice.

Tanaka Scientific Limited
7-10-3, Ayase, Adachi-ku, Tokyo, 120-0005 JAPAN
TEL : +81-3-3620-1711 E-mail: overseas-group@tanaka-sci.com
FAX: +81-3-3620-1713 URL : www.tanaka-sci.com